

## Designed for Healthcare

Wallbox

Dripless quick connect, hose bib, or custom connections ensure compatibility with your machines

Spacious drain tray eliminates drips and spills when connecting or disconnecting

Drain block ensures compliant air gap

Optional onboard indication provides confidence when connecting machines to outlets

Low profile side entry wallbox design reduces installed depth and allows for integration in standard stud walls or regular depth millwork

Recessed bulkhead fittings eliminate unnecessary strain on connections and accidental damage to equipment





## **Specifications**

Dimensions 16 3/4" W x 15 3/4" H x 5" D (plus piping allowances)

Cutout Dimensions  $14 \frac{1}{2}$ " W x 15  $\frac{1}{2}$ " H x 5  $\frac{1}{2}$ " D

Weight (Approx) 10 lbs

Material (Wallbox) Polycarbonate

Material (Fittings) 316 SS (quick connect), nylon (hose bib)

Machine Inlet Connections Dripless quick connect / hose bib / custom

Machine Drain Connections Dripless quick connect / hose bib / custom

Box Drain Outlet Sink strainer (tailpiece connection)

Ambient Operating Temperature 15-40 C

Storage Temperature 5-50 CInlet Water Temperature 5-40 C

## **Options**

Single or Dual Outlets Quick connect, hose bib, or custom connections Remote Indication



